


# V16 Continuous Transmitters



## Multi-purpose transmitter for medium and large species



The **V16 continuous transmitter** is a multi-purpose, 16 mm diameter tag. Developed for real-time tracking, it can function as a simple pinger giving location only, or for more detailed research programs, it can also be equipped with a depth and/or temperature sensor. Depending on the battery size and ping period, the tag will last several days to multiple years and give a transmission range in excess of one kilometer (this varies significantly with environmental conditions). Given its size, the V16 is best suited for studies involving medium to large species. V16 continuous tags are used with the VR100 active tracking receiver.



V16 transmitter

### Continuous Mode

In continuous transmission mode, the acoustic ping is transmitted after a fixed period interval that is factory pre-set and typically between one and two seconds. This mode is ideal for real-time tracking studies. V16 continuous pingers and continuous data telemetry (temperature and depth) transmitters are available in several frequencies: 51.0, 54.0, 57.0, 60.0, 63.0, 75.0, 78.0, 81, 84 kHz.

### V16 Continuous Tag Options


For research requiring temperature and depth information, V16 tags can be equipped with temperature (V16T), depth (V16P), or both temperature and depth sensors (V16TP). V16P pressure tags are available in several full scale pressure options: 17, 34, 68, 136, 204, 340, and 680 meters. V16T temperature tags are available in four temperature ranges: -5 to 35°C, -4 to 20°C, 0 to 40°C and 10 to 40°C.

### Physical Specifications

The physical measurements of the V16 vary with battery option and whether temperature or pressure sensors are included. Specifications are shown in the table below.

Battery Option:		Silver Oxide		Lithium					
		1L	1H	4L	4H	5L	5H	6L	6H
<b>V16/V16T</b>	Length (mm)	54	54	68	68	95	95	95	95
<b>V16P/ V16TP</b>	Length (mm)	54	54	71	71	98	98	98	98
<b>All V16s</b>	Power Output (dB re 1uPa @1m)	150	156	152	158	157	162	152	158
	Weight in water (g)	9		11		16		16	
	Weight in air (g)	20		25		36		36	

Stated tag length, weight and output power are nominal. Small manufacturing variations can be expected.



Tel: (902) 450-1700  
Fax: (902) 450-1704

www.vemco.com

Temperature Sensor		
Range	Accuracy	Resolution
-5 to 35 °C	±0.5 °C	0.15 °C
-4 to 20 °C	±0.5 °C	0.1 °C
0 to 40 °C	±0.5 °C	0.15 °C
10 to 40 °C	±0.5 °C	0.12 °C

Pressure Sensors (at room temperature)		
Max Depth	Accuracy	Resolution
17 m	±1.7 m	0.08 m
34 m	±1.7 m	0.15 m
68 m	±3.4 m	0.3 m
136 m	±6.8 m	0.6 m
204 m	±10 m	0.9 m
340 m	±17 m	1.5 m
680 m	±34 m	3.0 m

### Expected Battery Life

The life span of the V16 transmitter will vary significantly with battery size [1, 4, 5 or 6], power output [H or L], ping period and the presence/absence of a data sensor. Life span for each option in days is listed in the table below.

### External Case



Period	V16 Continuous Tags Battery Life (Days)							
	V16 Pingers							
	V16-1L	V16-1H	V16-4L	V16-4H	V16-5L	V16-5H	V16-6L	V16-6H
1000 ms	52	16	390	112	212	64	752	218
2000 ms	97	32	728	220	403	126	1389	426
Period	V16 Sensor Transmitters							
	V16TP-1L	V16TP-1H	V16TP-4L	V16TP-4H	V16TP-5L	V16TP-5H	V16TP-6L	V16TP-6H
1000 ms	32 (22)	14 (9)	235 (161)	97 (66)	158 (108)	60 (41)	454 (312)	189 (128)
Period	V16P-1L	V16P-1H	V16P-4L	V16P-4H	V16P-5L	V16P-5H	V16P-6L	V16P-6H
	1000 ms	17 (8)	10 (5)	123 (61)	69 (34)	97 (48)	47 (23)	239 (119)
2000 ms	33 (21)	19 (12)	241 (151)	137 (85)	190 (119)	94 (58)	466 (294)	265 (165)
Period	V16T-1L	V16T-1H	V16T-4L	V16T-4H	V16T-5L	V16T-5H	V16T-6L	V16T-6H
	1000 ms	49 (25)	16 (8)	368 (187)	110 (55)	205 (103)	64 (31)	709 (362)
2000 ms	92 (59)	31 (19)	688 (447)	216 (136)	392 (251)	125 (78)	1315 (859)	419 (263)

Notes: The projected battery life is an estimate and users will experience a decrease in battery life if their tags are operating in extreme warm or extreme cold temperatures.

VEMCO transmitters are programmed to stop transmitting when they reach their stated battery life. This ensures that tags will operate at published specifications until expiration.

VEMCO tags are warranted to be free from defects in material and workmanship for one year from date of delivery.

V16 tags with sensors will ping at varying rates depending on the sensor readings and therefore battery life will vary depending on the behaviour of the animal. The two battery lives shown for sensor tags are the extremes. Consult your VEMCO representative to determine the expected battery life for your study and for additional information regarding battery life.